STEAM GENERATOR

SPECIFICATION SHEET

Made in the USA by Amerec, a leading manufacturer of steam and sauna equipment

Features:

- Stainless steel tank and water level probes provide years of trouble-free operation
- Removable heating elements provide easy and economical service
- Custom Foeder Crafters control allows for extended steaming of barrels
- Small size allows unit to be moved easily
- ETL listed for USA and Canada
- Tested to IEC standards
- One-year commercial warranty

Electrical Information:

- 8-foot 220v locking L6-30P power adapter installed
- 30A dedicated circuit required
- Can be hard wired in the field for 208-240v 1/3 phase power

Plumbing Information:

■ Water inlet: ³/₈" NPT

• Steam outlet: 1½" tri-clamp adapter

Pressure relief: ¾" NPTDrain outlet: ¾" NPT

Installation:

- Install in dry, well ventilated area.
- Install generator level, on its base or hung on a wall.
- Provide adequate access for service.
- Run cold (preferably conditioned) water line with shut off valve.
- Run steam line as short as possible. Slope pipe/hose to avoid creating condensation build up. Do not create traps or pipe obstructions.
- Run ¾" pressure relief and drain lines in accordance with codes.

Dimensions and weight:

- 16½" x 15" x 6¼"
- 35 lbs.



FOEDER CRAFTERS
OF AMERICA

ESTD. 2013

